

## Technical Data Sheet\_ 60W LED Panel (Bottom opening Cleanroom)



### Product Details

Code : 60W LED Panel (Cleanroom)  
Model : Panel Light  
Make : SHINE PLUS

### Electrical Data

Power Consumption : 60W  
Operating Voltage Range : 90VAC-265VAC  
Frequency : 50 Hz  
Power Factor : > 0.96  
Driver : Constant Current (Internal)  
Efficiency : > 85%

### Light Data

Light source (LED) : Edison  
Efficacy : 110 lm/Watt  
Luminous flux : 6600 lumens  
Colour temperature : 6000k  
CRI : >80  
Average Life : L70 @ 50,000 Hours.

### Environmental

Working Temperature : 0 °C to + 55 °C  
Working Humidity : 10 to 90% RH  
Storage Temperature : 0°C TO + 85 °C  
IP Rating : IP20 Protected from touch by fingers  
and objects greater than 12MM.  
Not protected from liquids

### Protection

Output Overvoltage/Under voltage : Protected  
Output Short circuit : Protected  
Surge Protection : Protected (4KV)

### Physical Details


Material : Aluminium Die cast  
Dimensions : 580 x 580 mm (cut out)  
650 x 650 mm (outer)  
75 mm height

Suitable Fixing : Mount Suitable for any ceiling

### Applications

Application Area : Indoor  
Commercial and residential premises  
Offices/ banks  
Hotels and restaurants  
Shops and showrooms

Warranty : 2 Years



[www.shineplusled.com](http://www.shineplusled.com)



